

HISTORICAL

Terminal Blocks - Component

COMPANY

KORNER SRL

Via Volta 12

Cusago, MI 20047 Italy

E73420

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
OK133 f/b /1 thru /5, may be f/b LP	14-16, 12-18	Cu	2	5	600	6.3	B, C	2(105), 4
		Cu	2	8	600	20	B, C	2(105), 4
CS900, CS910, CS920, C930	12-22(1)	Cu	2	7	300	15	B, D	2(105), 4
OK431NY, OK431NY-F	14-20	Cu	2	5	300 600	15	B, C D	2(115), 4
OK431NY-LP, OK431NY-FLP	16-20	Cu	2	5	300 600	10	B, C D	2(115), 4
OK431FV	14-20 Str, 20 Sol	Cu	2	5	300 600	15	B, C D	2(120), 4
OK431FV-LP	16-22 Sol, 22 Str	Cu	2	5	300 600	15	B, C D	2(120), 4
OK432FV, OK432FV-LP	14-20	Cu	2	4	600	15	B, C	2(115), 4
OK432NY, OK432NY-LP	14-20	Cu	2	6	600	15	B, C	2(105), 4
OK433FV, OK433NY-LP	12-18	Cu	2	8	300 600	20	B, C D	2(120), 4
OK433FV-LP	12 Str only	Cu	2	8	300 600	20	B, C D	2(120), 4
OK433FV-LP	12-18 Sol.	Cu	2	7	300 600	20	B, C D	2(120), 4
OK433FV-LP	18 Str only	Cu	2	7	300 600	20	B, C D	2(120), 4
OK433FV-HLP	12-18	Cu	2	5	300 600	20	B, C D	2(120), 4
OK433NY	12 Str only	Cu	2	8	300 600	20	B, C D	2(115), 4

OK433 NY	12-18 Sol.	Cu	2	7	300 600	20	B, C D	2(115), 4
OK433 NY	18 Str only	Cu	2	7	300 600	20	B, C D	2(115), 4
OK433NY-HLP	12-18 Str, 18 Sol	Cu	2	8	300 600	20	B, C D	2(115), 4
OK433NY-HLP	12 Sol.	Cu	2	7	300 600	20	B, C D	2(115), 4
OK433 NY-F, OK433 NY-F-LP	12-18 Sol/Str	Cu	2	7	300 600	20	B, C D	2(115), 4
OK433 FV-F, OK433 FV-FLP	12-18 Sol/Str	Cu	2	7	300 600	20	B, C D	2(120), 4
OK433 FV-H	12-18	Cu	2	7	300 600	20	B, C D	2(120), 4
OK433NY-H	12-18	Cu	2	7	300 600	20	B, C D	2(115), 4
OK403 SP-LP	12-18 Sol/Str	Cu	2	8	300 600	20	B, C D	2(115), 4
OK434FV	8-14	Cu	2	10	300 600	40	B, C D	2(120), 4
OK434FV-LP	10-16	Cu	2	8	300 600	30	B, C D	2(120), 4
OK434NY-LP	16-10	Cu	1	8	300 600	30	B, C D	2(115), 4
OK434NY	8-14	Cu	2	10	300 600	40	B, C D	2(115), 4
OK435FV, OK435FV-LP	6-14	Cu	2	18	600	65	B, C	2(120)
OK435NY, 435NY-LP	6-14	Cu	2	18	600	65	B, C	2(115), 4
OK438NY	4-8 Str only 10-12 Sol/Str	Cu	2	21	600	80	B, C	2(105), 4
OK501, OK508	18-12 —	Cu Cu	2 2	10.6 —	300 300	16 16	B, C B, C	1, 2(105), 4 2(105)
PL2.5/32-35	14 Sol/Str- 12 Sol	Cu	1	7	600	25	B, C	2(105)
PL4/32-35	12 Sol/Str- 10 Sol	Cu	1	7	600	30	B, C	2(105)
PL6/32-35	10 Sol/Str- 8 Str	Cu	1	7	600	42	B, C	2(105)
PL10/32-35	8-6 Str	Cu	1	12	600	50	B, C	2(105)
PL16/32-35	4-6 Str	Cu	1	12	600	65	B, C	2(105)
PL35/32-35	2 Str	Cu	1	12	600	90	B, C	2(105)

PL70/32-35	2/0 Str	Cu	1	150	600	140	B, C	2(105)
CS990, f/b 1-12, f/b LP	4-12 Str	Cu	1/2	21	600	85	B, C	2(105), 4
	14 Str	Cu	1/2	18				
	10-12 Sol	Cu	1/2	21				
	14 Sol	Cu	1/2	18				
TE4	12-22	Cu	2	7	#	#	B, C	2(105), 4
TE6	10-20	Cu	2	7	#	#	B, C	2(105), 4
TE10	8-16	Cu	1	12	#	#	B, C	2(105)
TE16	4-14	Cu	1	12	#	#	B, C	2(105)
OK200 FV-LPSP	12-18 sol/str	Cu	2	8	300	15	B, C	1,2(115), 4
	14-20 sol/str (2)	Cu	2	N/A	300	15	B, C	1,2(115), 4
CS992 followed by 2 or 3	20-10	Cu	2	20	600	101	B, C	2(110)
	8-2 str	Cu	2	27.5	600	101	B, C	2(110)
OK 650, followed by NY	12-22 sol/str	Cu	2	10.6	300 150	20	B, D C	1, 2(105), 4
OK 650, followed by NY S	12-22 sol/str	Cu	2	10.6	300 150	20	B, D C	1, 2(120), 4
OK280, OK280/A	20-8 sol/str	Cu	2	20	600	40	B, C	1, 2(120), 4
OK201/ FVLP, OK201/ FV	12-18 sol/str	Cu	2	8	300	15	B, C	1,2(115), 4
	14-20 sol/str (2)			N/A				
OK201/ NYLP, OK201/ NY	12-18 sol/str	Cu	2	8	300	15	B, C	1,2(100), 4
	14-20 sol/str (2)			N/A				
OK401	(3)	Cu	1	N/A	300	20	B,C,D	1, 2(105)

Note (1): Wire range includes No. 26 AWG wire for factory-wiring applications only.

These types are for grounding applications and have no assigned voltage and ampere rating.

Note (2): Wire Secured by Spring Type Action.

Note (3): these devices are provided with quick connect tab terminals evaluated for use with quick connect female terminals using 12AWG STR.

Series OK403, OK431, OK432, OK433, OK434, OK435, OK438 and OK501 are followed by one or two digits denoting the number of poles.

Note for usage Group D: These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.

Marking: Company name or trademark  and catalog designation (catalog designation may appear on shipping carton).

Last Updated on 2023-10-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."