

Poliammide **PA6.6** nera
Autoestinguente **UL94V0**
GWIT775°C (EN 60695-2-13)
Temperatura di esercizio **T105°C**
Bussole o contatti in ottone OT58
nichelato
Viti in acciaio zincato
Guarnizioni in silicone
IP68 per 120h a 4mt

Black polyamide **PA6.6**
Self-extinguishing **UL94V0**
GWIT775°C (EN 60695-2-13)
Working temperature of **T105°C**
Inserts or contacts in brass OT58,
nickel plated
Screws in zinc plated steel
Silicone waterproof rubbers
IP68 for 120h at 4mt



Approvazioni / Approvals



CEI EN 60998-1 / CEI EN 60998-2-1 / CEI EN 62444



UL2238

Legenda delle quote
Legend for dimensions

Descrizione / Description	Art		Art		Art		Art		Art	
Connettore Connector	OK-L02		OK-L03		OK-T02		OK-T03		OK-B02	
Numero poli e codice Number of poles and code	2p	4575200	3p	4575300	2p	4576200	3p	4576300	2p	4577200
Tipologia di connessione Type of connection	a vite - screw type				rapida - screwless quick wiring					
Specifiche tecniche Technical characteristics	2,5mm ² - 24A - 400V				1,5mm ² - 17,5A - 450V				1,5mm ² - 17,5A - 450V	
	14AWG - 20A - 300V				16AWG - 15A - 300V				16AWG - 15A - 300V	
A Lunghezza / Length	58 mm				66 mm				58 mm	
B Larghezza / Width	26 mm				27,5 mm				26 mm	
C Vite / Screw	M 2,5									
D Foro bussola Bush hole	Ø 2,8 mm									
Accessori / Accessories:										
Diametro foro gommini standard e range dei cavi Standard rubbers diameter and cables range	Ø 6,5 mm (3,5 - 7 mm)				Ø 8,5 mm (5 - 9 mm)				Ø 6,5 mm (3,5 - 7 mm)	
Altri gommini disponibili Other available rubbers	Ø 9,8 mm (7 - 10 mm)				Ø 11,5 mm (9 - 12 mm)				Ø 9,8 mm (7 - 10 mm)	
Note / Notes:										
Diametro dima di foratura Drilling template diameter	Ø 16,6 mm				Ø 16,6 mm				Ø 16,6 mm	
Confezione e imballo Packing and box	50 / 600 pz/pcs				50 / 600 pz/pcs				50 / 600 pz/pcs	